


NRSE Series

CHARACTERISTICS



Satura on Satura on

		(m)		(m)	
3.10	2.80	3.70	3.30	4.00	
2.90	2.40	3.00	4.10	480	
2.60	2.30	2.30	500	600	
2.20	2.00	1.95	630	760	
1.60	1.45	1.65	960	114	
1.20	1.10	1.35	145	174	
1.15	1.05	1.20	215	265	
0.95	0.85	1.00	290	345	
0.80	0.70	0.75	400	480	
0.60	0.55	0.70	610	800	
0.60	0.53	0.68	730	940	
0.60	0.50	0.65	800	1000	
0.42	0.36	0.62	1100	1430	
0.38	0.30	0.50	1300	1700	
0.36	0.30	0.32	1400	1700	

	(μH)							
NRSE2016-R24M	0.24							
NRSE2016-R33M	0.33							
NRSE2016-R47M	0.47							
NRSE2016-R68M	0.68							
NRSE2016-1R0M	1.00							
NRSE2016-1R5M	1.50							
NRSE2016-2R2M	2.20							
NRSE2016-3R3M	3.30							
NRSE2016-4R7M	4.70							
NRSE2016-6R8M	6.80							
NRSE2016-8R2M	8.20							
NRSE2016-100M	10.0							
NRSE2016-120M	12.0							
NRSE2016-150M	15.0							
NRSE2016-220M	22.0							

Operating temperature: -40°C ~ +125°C

Temperature rise current: the actual value of DC current when the temperature rise is T40C

Saturation Current that will cause initial inductance to drop approximately 30%

